

Barometric Pressure Sensor *standard*



Description

Very accurate and rugged sensor for the measurement of barometric pressure.

The atmospheric pressure deforms a sensing element. An electronic transducer converts the raw signal and provides a voltage linearly dependent on the barometric pressure.

In addition to the analog output a digital port permits the direct connection of the sensor to a PC or the data logger **blueberry NDL 485**.

Technical Data

Sensor

Sensing element	Aneroid sensor
Transducer	Electronical transducer with voltage output
Analog output	600..1100 hPa = 0..5 V, range can be modified by the user
Digital output.....	RS232 / RS485 serial port, 9600 baud
Minimum load resistor.....	> 10 kOhm

Accuracy

Maximum inaccuracy.....	±0.3 hPa at 20 °C
	±0.5 hPa at -50..+60 °C

Power Supply

Supply voltage.....	7..30 VDC
Current consumption	10 mA
Warmup time	2 s

Casing

Material	Plastic
Protection class.....	IP 20
Dimensions	120 x 120 x 60 mm
Weight	0.35 kg

Electrical Connection

Cable 3 x 0.5 mm²
Terminals..... Open terminated wires

Wiring

white (+) power supply
brown..... Ground
green Output

Environmental Conditions

Operating temperature..... -50..+60 °C
Relative humidity..... 0..100%

Characteristics for Data Logger wilog303/306

Please enter the following function when the sensor is used with **wilog303** or **wilog306** data loggers.

Example: Connection to analog Input f

pBaro : mean = 600 + 100 * f



Wilmers Messtechnik GmbH
Hirschgraben 24
D-22089 Hamburg • Germany
phone: +49(0)40-75 66 08 98
fax: +49(0)40-75 66 08 99
eMail: info@wilmers.com
www.wilmers.com