

Global Radiation Sensor CM3



Description

Rugged pyranometer for the measurement of global radiation, the sum of both the direct and diffuse components of solar irradiance.

A set of thermocouples measure the temperature of a horizontal surface exposed to sunlight. An electronic transducer converts the raw signal into a voltage linearly dependent on incident solar power.

The sensor meets „WMO Second Class“.

Technical Data

Sensor

Sensing element.....	Thermocouples
Transducer.....	Electronical transducer with voltage output
Output signal	0..1400 W/m ² = 0..5 V
Output load	> 10 kOhm
Spectral response.....	300..2800 nm
Viewing angle	2 PI steradian

Accuracy

Non-linearity	0..1000 W/m ² ± 2.5 %
---------------------	----------------------------------

Power Supply

Supply voltage	9..18 VDC
Current consumption	Approx. 10 mA

Casing

Material.....	Aluminium
Dome	Simple glass dome
Protection class	IP 65
Weight	Approx. 1 kg
Mounting	2 holes for fixing screws

Electrical Connection

Cable..... 4 x 0.25 mm² , shielded
Cable length..... 2 m
Terminals..... Open wires

Wiring

white..... (+) power supply
brown (–) power supply
green..... (+) output
yellow..... (–) output (ground)
yellow/green Cable screen

Environmental Conditions

Operating temperature –45..+80°C
Relative humidity 0..100%

Compliance

The sensor meets „WMO Second Class“ (WMO = World Meteorological Organisation).



Hirschgraben 24
D-22089 Hamburg • Germany
phone: +49(0)40-75 66 08 98
fax: +49(0)40-75 66 08 99
eMail: info@wilmers.com
www.wilmers.com